



FOLDED GRID 003

GRD-FLD-003

Product Specifications

Product Name	Folded Grid 003					
Product ID	GRD-FLD-003					
Acoustics	0.95 - 1.00 NRC*					
Lead Time	Lead time is dependent on project size. Contact us for more information.					
Durability	Contract					

Warranty	Comes with industry-leading standard warranty.				
Flammability	ASTM E84: Class A				
Custom	Custom colors and manufacturing services available. Additional charges and lead times may apply.				
	Vacuum occasionally to remove airborne dust or debris. Mild detergents or soaps may be used to remove stains. For detailed care instructions, refer to the CSI Creative Maintenance Information document.				

Material Specifications

	Soundcore®
Content	Recycled PET acoustic felt
Weathering	Colorfast, non-deteriorating, non-hygroscopic
Entri officiation	Recycled PET acoustic felt is 60% post-consumer recycled content and is 100% recyclable. Contributes points toward LEED v4. CDPH v1.2, VOC free, non-toxic, non-allergenic, anti-microbial - does not attract mold and mildew. Compliant with Living Building Challenge criteria & DECLARE Red List Free.
	PET felt panels are created through a manufacturing process known as 'felting'. This process results in a heathered appearance. Multiple color tones may appear in the same panel. Slight color variations should be expected.






*Approximate. NRC rating may vary due to product dimensions and spacing.



Dimensions


Standard Unit Dimensions

Typical ranges for length and width.



Standard Unit Thicknesses

Thickness is independent of material layer selection.




Custom Opportunity

Product dimensions can be manipulated in order to fit your design aesthetic and site conditions.



Product Details







Configuration Options

Categories

The categories shown represent the available options for this product.





Depth




Installation Options

All products and installation methods can be customized to meet the unique requirements of your space.

Drop-In

- + Replaces existing mineral tiles
- + Substrate based, no hardware needed



*Not all listed attachment methods may be applicable to this product.



Material Layers

Soundcore®

Our recycled PET felt creates an acoustic barrier, defending against wandering white noise and irritating echoes.






Single Layer ½" Thickness

Soundcore® Wood Textures

Soundcore[®] wood textures provide the natural aesthetic of wood while maintaining all the acoustic benefits of PET felt. Custom texture opportunities are also available upon request.



Single Layer ½" Thickness





Folded Grid 003 | GRD-FLD-003

Soundcore® | 1/2" Thickness

SND019	SND037	SND135	SND135	SND105	SND109	SND111	SND130	SND131	SND125
Linen	Paper	Oat	Vanilla Bean	Sand Dollar	Macadamia	Lanai	Buckskin	Abalone	Chinchilla
SND118	SND126	SND110	SND102	SND114	SND034	SND132	SND103	SND038	SND122
Anchor	Wolfhound	Starry Night	Morning Fog	Lunar Dust	Granite Peak	Cast Iron	Storm Cloud	Inkwell	Briquette
SND127	SND108	SND104	SND106	SND113	SND107	SND136	SND129	SND115	SND137
Burnt Toast	Ablaze	Pumpkin	Goldfinch	Gruner	Grasshopper	Clover	Dried Thyme	Mako	Cove
SND112	SND121	SND123	SND117	SND124	SND128	SND133	SND116	SND101	SND042
Tulum	Apatite	Chrysocolla	Serene	Ice Floe	Arctic Ocean	Galactic	Blue Marlin	Commodore	Denim



Soundcore® Wood Textures | 1/2" Thickness











SND713





SND790

Natural Teak



SND716 Dark Teak

SND711

Bleached Cherry

SND792 Dark Oak

SND715 Dark Cherry

SND794 Warm Teak

SND793

Vintage Maple

SND791

Gray Oak

SND714 English Walnut

Honey Walnut

SND717 Warm Oak

SND712 Natural Spruce





SND795

Light Teak



SND709 White Maple

SND710 Gray Teak

