



FOLDED GRID 020

GRD-FLD-020

Product Specifications

| Product Name | Folded Grid 020 | Warranty | Comes with industry-leading standard warranty. |
|--------------|--|--------------|---|
| Product ID | GRD-FLD-020 | Flammability | ASTM E84: Class A |
| Acoustics | 0.75 - 0.85 NRC* | Custom | Custom colors and manufacturing services available. Additional charges and lead times may apply. |
| Lead Time | Lead time is dependent on project size. Contact us for more information. | | Vacuum occasionally to remove airborne dust or debris. Mild detergents or soaps may be used to remove stains. For detailed care instructions, refer to the CSI Creative Maintenance Information document. |
| Durability | Contract | | |

Material Specifications

| | Soundcore® |
|---------------------|---|
| Content | Recycled PET acoustic felt |
| Weathering | Colorfast, non-deteriorating, non-hygroscopic |
| Ziivii Oiliiioiitai | Recycled PET acoustic felt is 60% post-consumer recycled content and is 100% recyclable. Contributes points toward LEED v4. CDPH v1.2, VOC free, non-toxic, non-allergenic, anti-microbial - does not attract mold and mildew. Compliant with Living Building Challenge criteria & DECLARE Red List Free. |
| | PET felt panels are created through a manufacturing process known as 'felting'. This process results in a heathered appearance. Multiple color tones may appear in the same panel. Slight color variations should be expected. |





Declare.



*Approximate. NRC rating may vary due to product dimensions and spacing.




800. 213. 0653 info@csicreative.com csicreative.com Page 2

Dimensions

Standard Unit Dimensions

Typical ranges for length and width.




Custom Opportunity

Product dimensions can be manipulated in order to fit your design aesthetic and site conditions.

Standard Unit Thicknesses


Thickness is independent of material layer selection.





800. 213. 0653 info@csicreative.com csicreative.com Page 3

Product Details






Installation Options*

All products and installation methods can be **customized** to meet the unique requirements of your space.

Press-Fit

+ Substrate based, no hardware needed




*Not all listed attachment methods may be applicable to this product.



Material Layers

Soundcore®


Our recycled PET felt creates an acoustic barrier, defending against wandering white noise and irritating echoes.





Soundcore® Wood Textures

Soundcore® wood textures provide the natural aesthetic of wood while maintaining all the acoustic benefits of PET felt. Custom texture opportunities are also available upon request.




Single Layer
½" Thickness



Elements

Refined finishes and subtle sheens bring depth and dimension to any space.





Soundcore® | 1/2" Thickness





800.213.0653 info@csicreative.com csicreative.com Page 7

Soundcore® Wood Textures | 1/2" Thickness



SND716 Dark Teak



SND792 Dark Oak



SND715 Dark Cherry



SND793 Vintage Maple



SND794 Warm Teak



SND714 English Walnut



SND795 Light Teak



SND711 Bleached Cherry



SND713 SND796 Honey Walnut Vintage Cherry



SND717 Warm Oak



SND790 Natural Teak



SND712 Natural Spruce



SND709 White Maple



SND791 Gray Oak



SND710 Gray Teak



csicreative.com Page 8

Elements

