



FOLDED PLUG GRID 010

Product Specifications

Product Name	Folded Plug Grid 010	Warranty	Comes with industry-leading standard warranty.
Product ID	GRD-FPG-010	Flammability	ASTM E84: Class A
Acoustics	1.05 NRC*	Custom	Custom colors and manufacturing services available. Additional charges and lead times may apply.
Lead Time	Lead time is dependent on project size. Contact us for more information.		Vacuum occasionally to remove airborne dust or debris. Mild detergents or soaps may be used to remove stains. For detailed care instructions, refer to the CSI Creative Maintenance Information document.
Durability	Contract		

Material Specifications

	Soundcore®	PoshFelt®
Content	Recycled PET acoustic felt	100% Merino or Karakul wool acoustic felt
Weathering	Colorfast, non-deteriorating, non-hygroscopic	Colorfast, non-deteriorating, non-woven, moisture resistant
Environmental	Recycled PET acoustic felt is 60% post-consumer recycled content and is 100% recyclable. Contributes points toward LEED v4. CDPH v1.2, VOC free, non-toxic, non-allergenic, anti-microbial - does not attract mold and mildew. Compliant with Living Building Challenge criteria & DECLARE Red List Free.	100% organic wool design felt is a rapidly renewable resource and is 100% biodegradable/compostable. Contributes points toward LEED v4. CDPH v1.2, VOC free, no chemical irritants, no formaldehyde, and is free of other harmful substances. Compliant with Living Building Challenge criteria & DECLARE Red List Free.
Variation	PET felt panels are created through a manufacturing process known as 'felting'. This process results in a heathered appearance. Multiple color tones may appear in the same panel. Slight color variations should be expected.	Due to its 100% natural origin, the raw fibers of wool felt contain inclusions and color variations throughout the material. Color matching is not guaranteed between dye lots and inconsistencies may be more prominent in volumes that exceed the normal commercial standard.







*Approximate. NRC rating may vary due to product dimensions and spacing.




800.213.0653 info@csicreative.com csicreative.com Page 2

Dimensions

Standard Unit Dimensions

Typical ranges for length and width.




*Available in lengths of 24" & 48"

Custom Opportunity

Product dimensions can be manipulated in order to fit your design aesthetic and site conditions.

Standard Unit Thicknesses


Thickness is independent of material selection






800. 213. 0653 info@csicreative.com csicreative.com Page 3

Units






Product Details





Configuration Options

The layouts shown are a summation of individual units. Individual units may be assembled in various arrangements to dictate the larger design. Configurations shown are suggested, but can be rearranged to achieve a custom layout.



Uniform Random




Installation Options*

All products and installation methods can be **customized** to meet the unique requirements of your space.

Above Grid Installation

- + Easy to install, adjust, and remove
- + Replaces existing mineral tiles
- + Substrate based, no hardware needed


Available methods: Drop-In



Below Grid Installation

- + Visually obstructs metal grid structure
- + 1/4" gap between tiles

Available methods: Press-Fit



*Not all listed attachment methods may be applicable to this product.




800. 213. 0653 info@csicreative.com csicreative.com Page 7

Material Layers

Soundcore®


Our recycled PET felt creates an acoustic barrier, defending against wandering white noise and irritating echoes.





Soundcore® Wood Textures

Soundcore® wood textures provide the natural aesthetic of wood while maintaining all the acoustic benefits of PET felt. Custom texture opportunities are also available upon request.




Single Layer
½" Thickness



PoshFelt® Exposed Edge


100% organic, natural wool design felt brings out the best experience in your space with color, comfort, and simple sustainability. Exposed edge products leave the Soundcore® layer uncovered, allowing for unique color combinations.



Multi-Layer
Adds 1/8" - 1/4" to Material Thickness



PoshFolt® | 3mm Thickness



PoshFolt® | 3mm Thickness



PoshFolt® | 3mm Thickness



PoshFolt® | 8mm Thickness



Soundoore® | 1/2 Thickness



Soundoore® Wood Textures: | 1/2" Thickness



- SPECTIA Buylish Walson Heroy Widow

STEATUT Windows Cont. .EXCUSES