



**FOLDED SURFACES 002** 

SUR-FLD-002

# **Product Specifications**

Product Name	Folded Surfaces 002	Warranty	Comes with industry-leading standard warranty.
Product ID	SUR-FLD-002	Flammability	ASTM E84: Class A
Acoustics	0.90 NRC*	Custom	Custom colors and manufacturing services available. Additional charges and lead times may apply.
Lead Time	Lead time is dependent on project size. Contact us for more information.		Vacuum occasionally to remove airborne dust or debris. Mild detergents or soaps may be used to remove stains. For detailed care instructions, refer to the CSI Creative Maintenance Information document.
Durability	Contract		

# **Material Specifications**

	Soundcore®
Content	Recycled PET acoustic felt
Weathering	Colorfast, non-deteriorating, non-hygroscopic
	Recycled PET acoustic felt is 60% post-consumer recycled content and is 100% recyclable. Contributes points toward LEED v4. CDPH v1.2, VOC free, non-toxic, non-allergenic, anti-microbial - does not attract mold and mildew. Compliant with Living Building Challenge criteria & DECLARE Red List Free.
Variation	PET felt panels are created through a manufacturing process known as 'felting'. This process results in a heathered appearance. Multiple color tones may appear in the same panel. Slight color variations should be expected.





Declare.



\*Approximate. NRC rating may vary due to product dimensions and spacing.




800.213.0653 info@csicreative.com csicreative.com Page 2

## **Dimensions**

#### **Standard Unit Dimensions**

Typical ranges for height and width.



### **Standard Unit Thicknesses**


Thickness is independent of material layer selection.

### **Custom Opportunity**

Product dimensions can be manipulated in order to fit your design aesthetic and site conditions.




## **Product Details**






# **Configuration Options**

The layouts shown are a summation of individual units. Individual units may be assembled in various arrangements to dictate the larger design. Configurations shown are suggested, but can be rearranged to achieve a custom layout.





## **Installation Options\***


All products and installation methods can be **customized** to meet the unique requirements of your space.

### **Adhesive Direct Advantages**

Attachment solution using an adhesive to apply directly to an existing surface or substrate

- +Fastest installation time
- +No gap between target surface and product
- +Lowest profile installation option
- +Easiest to install
- +Most versatile installation option

Available methods: Construction Adhesive, Peel & Stick, Custom




### **Mechanical Direct Advantages**

Attachment solution using physical hardware to attach to an existing surface or substrate.

- +No clamping or dry time necessary
- +Easy to remove and does not damage the substrate when removed
- +Most appropriate installation solution for heavier products
- + Provides an opportunity for an air gap, which can increase the acoustic value of a product

Available methods: Z-Clips, Panel Clips, Standoffs, Screw & Washer, Magnet, Custom



\*Not all listed attachment methods may be applicable to this product.




800. 213. 0653 info@csicreative.com csicreative.com Page 6

# **Material Layers**

### Soundcore®

Our recycled PET felt creates an acoustic barrier, defending against wandering white noise and irritating echoes.





### Soundcore® Wood Textures

Soundcore® wood textures provide the natural aesthetic of wood while maintaining all the acoustic benefits of PET felt. Custom texture opportunities are also available upon request.



1/2" Thickness





info@csicreative.com csicreative.com Page 7

### Soundcore® | 1/2" Thickness





### **Soundcore® Wood Textures** | 1/2" Thickness



SND716 Dark Teak



SND792 Dark Oak



SND715 Dark Cherry



SND793 Vintage Maple



SND794 Warm Teak



SND714 English Walnut



SND713 Honey Walnut



SND717 Warm Oak



Natural Teak



SND712 Natural Spruce



SND711 Bleached Cherry



SND795 Light Teak



SND709 White Maple



SND791 Gray Oak



SND710 Gray Teak