




WOODLITE®
Cube 006| CLD-WFD-007

Why WoodLite?

WoodLite® features wood-look felted acoustic material made from our Soundcore® PET-felt. This collection offers an innovative alternative to traditional wood-based installations, while maintaining the emotional resonance of natural wood in indoor environments.





Product Specifications

Product Name	Cube 006	Warranty	Comes with industry-leading standard warranty.
Product ID	CLD-WFD-007	Flammability	ASTM E84: Class A
Acoustics	0.40 - 0.85 NRC*	Custom	Custom colors and manufacturing services available. Additional charges and lead times may apply.
Lead Time	Lead time is dependent on project size. Contact us for more information.	Maintenance	Vacuum occasionally to remove airborne dust or debris. Mild detergents or soaps may be used to remove stains. For detailed care instructions, refer to the CSI Creative Maintenance Information document.
Durability	Contract		

Material Specifications

	Soundcore®	
Content	Recycled PET acoustic felt	
Weathering	Colorfast, non-deteriorating, non-hygroscopic	
Environmental	Recycled PET acoustic felt is 60% post-consumer recycled content and is 100% recyclable. Contributes points toward LEED v4. CDPH v1.2, VOC free, non-toxic, non-allergenic, anti-microbial - does not attract mold and mildew. Compliant with Living Building Challenge criteria & DECLARE Red List Free.	
Variation	PET felt panels are created through a manufacturing process known as 'felting'. This process results in a heathered appearance. Multiple color tones may appear in the same panel. Slight color variations should be expected.	





Declare.



*Approximate. NRC rating may vary due to product dimensions and spacing.




800.213.0653 info@csicreative.com csicreative.com Page 3

Dimensions


Standard Unit Dimensions

Typical ranges for length and width.



Standard Unit Thicknesses

Thickness is independent of material layer selection.




Custom Opportunity

Product dimensions can be manipulated in order to fit your design aesthetic and site conditions.



Product Details





Attachment Methods*

Aircraft Cable


- + Fastest/easiest height adjustment
- + Largest height adjustment range
- + Height and angle versatility
- + Accommodates uneven ceiling surfaces and MEP


Threaded Rod


- + Reduced product sway
- + Height and angle versatility
- + Accommodates uneven ceiling surfaces and MEP

Mechanical Direct

- + Lowest profile installation method
- + Eliminates product sway
- + Connects to: Unistrut, ACT Grid, flat ceiling surfaces
- + Connections: Magnets, Grid Clips, Panel Clips, Metal Bracket, Custom







^{*}Not all listed attachment methods may be applicable to this product.




800.213.0653 info@csicreative.com csicreative.com Page 6

Material Layers

Soundcore® Wood Textures

Soundcore® wood textures provide the natural aesthetic of wood while maintaining all the acoustic benefits of PET felt. Custom texture opportunities are also available upon request.





800, 213, 0653

Soundcore® Wood Textures | 1/2" Thickness



SND716 Dark Teak



SND792 Dark Oak



SND715 Dark Cherry



SND793 Vintage Maple



SND794 Warm Teak



SND714 English Walnut



SND795 Light Teak



SND711 Bleached Cherry



SND713 SND796 Honey Walnut Vintage Cherry



SND717 Warm Oak



SND790 Natural Teak



SND712 Natural Spruce



SND709 White Maple



SND791 Gray Oak



SND710 Gray Teak

CSI Creative

800. 213. 0653 info@csicreative.com csicreative.com Page 8